



AREX BLIZZ

Finishes for Exterior Walls

Description

Redwop's AREX BLIZZ Advanced Anti-algal Weather Proof is a water-based, 100% Acrylic smooth emulsion with silicon additives that offers an anti-algal and high performance exterior wall finish.

Advantages

- **Colour Stay™ Technology**

AREX BLIZZ uses specially formulated high performance color pigments and binder technology, which offer excellent resistance to ultraviolet radiation. This ensures brighter, cleaner shades that will not fade, ensure your home continues to look beautiful over time.

- **Advanced Anti-algal Formula**

AREX BLIZZ contains an advanced Anti-algal Formula which fights the formation of algae and keeps away ugly black spots from your walls

- **Excellent Dirt Pick up Resistance**

AREX BLIZZ is designed with a unique Dirt Pick Up Resistance (DPUR) property. It fights dust from settling on the wall surface and thereby retains the initial beauty.

- **Seen**

AREX BLIZZ offers excellent sheen, giving your newly painted home a classy finish.

Uses

- Helps to kill the growth of algae and fungus, and retain the initial beauty of your walls.
- Fights dust from settling on the walls, helping them retain its beauty.

Limitations

- Do not apply when ambient temperature is less than 10°C.

Technical Information

PROPERTIES	RESULTS
Drying Time	Surface dry time 30min
Sheen levels	3-12 at 60 deg GH
Stability of thinned paint	To be used with in 24 hours
Coverage	1 coat @ 10-12 sq.m/l** 2 coats @ 5-6 sq.m/l**

** Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

Method of Application

• PRE PAINTING STEPS

- **PLASTER** New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.
- **CLEANING** Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. When the underlying surface exhibits chalkiness, in spite of thorough surface cleaning.

FILLING FOR CRACKS For filling cracks upto 3mm use Redwop's Seal Crack / Redoseal ACL.

- **FILLING FOR HOLES & DENTS** In case of dents and holes use Redwop's Wall Putty or a mix of white cement and fine sand in the ratio 1:3.

For exterior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use Redwop's Smarzkot Advanced before the top coat application.

• PAINT APPLICATION PROCESS

Apply AREX BLIZZ with the help of brush/roller on the prepared surface.

After first coat dry apply 2nd coat immediately to get better adhesion between two coats.

Allow the coating for full cure until 24 hours.

In areas of having extreme environment condition you are recommended to contact Redwop expert team further information.

HORIZONTAL SURFACES LIKE TOP OF WINDOWS, LEDGES SHOULD BE PAINTED WITH 3 COATS OF AREX BLIZZ FOR GREATER PROTECTION

Packaging

- AREX BLIZZ is supplied in 200ml, 1, 4, 10 & 20 lit. container.

Shelf Life

- 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664

PAINT

Redwop®