



BITUFLASH

APP polymer modified bituminous water proofing membrane sheet

Description

BITUFLASH is a sheet of selected bitumen with modified APP polymers to form a high quality tough bitumen waterproofing system. BITUFLASH can be applied by using torch on RCC and metal surfaces.

Advantages

- Asbestos free
- Easily and inexpensively applied
- Resistant to most naturally occurring chemicals
- Odorless and taint free when dry
- Excellent flexibility
- Used for over 30 years in a wide range of environments
- Excellent adhesion to most common building substrates

Uses

- Underground RCC construction
- Garden above ground
- Corrosion protection to metal surfaces

Compliance standard

- ASTM D 5147
- ASTM D 5
- ASTM D 36

Cleaning

- Clean all tools and equipment with cleaning agents immediately after use.

Technical Information

PROPERTIES	RESULTS
Appearance	Black roll
Flammable	Yes
Flesh point	225°C

Method of Application

- All surfaces to be waterproofed should be clean, sound and dry. Priming of good quality, dense concrete is not necessary but for non-ventilated and damp surface priming is necessary.
- All inflammable materials from roofs to be removed and good roofing practices should be followed.
- BITUFLASH are unfolded on the site and laid firmly on surface with tar based adhesives using blowtorches.

Coverage

- It will give coverage of 1m x10 m @ 2 mm thickness.

Packing

- It is supplied as Roll (3mm & 4mm mineral and non-mineral).

Shelf Life:

- 1 year from the date of manufacturing if stored in cool dry place under shaded area and if unopened sealed pack condition surface after completion of the preparation work.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664