



**STONE & TILE
ADHESIVES**



REDELTITE-R

Epoxy Stone Adhesive

Description

REDELTITE-R is a multipurpose two component room temperature curing adhesive of high strength and toughness. It is suitable for bonding a wide variety of metals, ceramics, glass, rubber, rigid plastics and most other materials in common use. It is a versatile adhesive for the craftsman as well as most industrial applications.

- Ease to use
- Durable bonding
- Useful in both industrial and residential application
- No effect on aesthetic view
- Versatile adhesive

Uses

- Stone on stone
- Glass on glass
- Ceramic tiles
- Rubber
- Plastic

Confirmed standard

- IS 15477:2019 (CM/L-7600053713)

Compliance standard

- EN 12004 & ISO 13007, ANSI A118.4

Technical Information

| PROPERTIES | STANDARD TEST METHOD | RESULTS |
|------------------|----------------------|--------------------|
| Mixed Appearance | - | Colourless Paste |
| Cure Time | - | 4 to 6 hours @23°C |
| Full Cure | - | 10 hours @23°C |

Method of Application

- The substrate surface must be free from oil, grease or any loosely adherent material. The strength and durability of a bonded joint are dependent on proper treatment of the surfaces to be bonded.
- Mix resin and hardener thoroughly & appropriately
- Apply mix directly with a spatula to the pretreated and dry joint surfaces.
- The joint components should be assembled and secured in a fix position as soon as the adhesive has been applied.
- All tools should be cleaned with hot water and soap before adhesives residues have had time to cure.

Packaging

- REDELTITE-R is supplied in 90 gm, 180 gm, 450 gm, 900 gm, 1.8 kg, 9 kg set.

Storage

- Minimum of 24 months shelf-life if kept under room temperature (i.e. 27°C).

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664