



REMOL EXTRA

Concentrated and emulsified chemical mould release agent

Description

REMOL EXTRA is supplied as a pale amber liquid which turns white when diluted with water to produce a chemical release agent.

Advantages

- No cleaning of unsightly oil stains if plastering is not required
- Produces really fair faced finish concrete
- Can be used on all types of moulds
- Reduces storage and transport costs
- Aids corrosion inhibition

Uses

- For easy and stain free release of concrete moulds and formwork of all types
- Wooden formwork is used and demolding or stripping times exceed 24 hours

Technical Information

PROPERTIES	RESULTS
Appearance	Light brown coloured liquid
Specific gravity	0.96 @ 20°C
Flammable	No
Staining	No

Method of Application

- First dilute REMOL EXTRA concentrate in the proportion of 1:6 with water, using a clean container and stirring thoroughly until evenly mixed.
- If the solution is not used the same day, it should be stirred again before use and may require very good stirring after 5 days.
- Apply the REMOL EXTRA 1:6 water dilution to the face of the formwork by spray, brush or cloth. Only one coat should be applied.

Coverage

- 1 lit REMOL EXTRA in 6 lit water will cover 800 ft².

Packaging

- It is supplied in 20, 50 & 200 lit pack.

Storage

- 1 year from the date of manufacturing if stored in cool dry place under shaded area and if unopened sealed pack condition surface after completion of the preparation work.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664

Redwop®

MOULD RELEASE AGENT