



SILICOREP WR100

Silicone based water repellent for exterior

Description

SILICOREP WR200 is composed of Siloxane & Silane polymers dispersed in water. It is used for waterproofing of concrete & cementitious vertical walls of building because it penetrates deeply into the substrate & provides an effective water repellent protective coating. It does not change the appearance of the substrate & the water repellent coating is UV resistant and durable.

Advantages

- Ease of application
- Ready to use, simply brushable or spray applied. Staining
- Clear coating does not stain the treated surface
- Does not change the appearance of exterior decorative coating
- Prevents entry of moisture into the wall, but allows moisture to evaporate out
- Prevent efflorescence
- Cost effective
- Due to low viscosity penetration is high, which provides the hydrophobic zone

Uses

- Water repellent treatment for
- Cement painted surfaces
- Concrete, mortar Clay brick surfaces
- Natural and artificial stones
- Mangalore tiled roofs Corrugated AC sheet roofing, etc.

Technical Information

PROPERTIES	RESULTS
Colour	Clean free flowing pale yellow liquid
Specific weight	1 @ 30°C
Dry time	20 to 30 minutes
pH	7 to 8

Method of Application

- Surface should be dry and free from all debris, dirt, oil, grease, wax and all other contamination, which could prevent penetration.
- Clean the saturated dirt of surface by thorough wire brushing, cleaning with compressed air followed by water washing.
- Apply one liberal coat of SILICOREP WR100, simply by brushing evenly on the prepared surface.
- Allow the surface to dry for a minimum of 24 hrs. for best results.
- SILICOREP WR100 can also be applied with an airless spray (0.07 – 0.1 N/mm² pressure).
- Apply second coat wet on wet, to improve the penetration rate & performance. Allow it to dry for 24 hrs
- Do not dilute with water or by any other means.
- Close the container lid properly after use. Before applying over the natural stones like sand stone, slate or Dholpur sampling should be done on a small area to check its suitability.
- Before taking up application on a large area, it is advisable to check the performance of the product on a relatively small area.

Coverage

- On porous substrate – 5 to 6 m²/ lit
On low porous substrate – 7 to 8 S m² / lit

Packaging

- It is supplied in 1, 10, 20, 50 & 200 litres pack.

Shelf Life

- Shelf life is 12 months in unopened packs stored at room temperature i.e.27°C.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664