



Description

PLASTCONE R is a chloride free concrete retarder which can delay the setting time of concrete. The initial hydration of the cement is also delayed, resulting in a delay in the setting time of the concrete with no adverse effect on subsequent stiffening and strength gain.

Advantages

- Controlled retardation extends working life and stiffening time for ease of construction
- Water reduction significantly improves compressive strengths at all ages and enhances durability through the production of low permeability concrete
- Control of stiffening improves slip forming and assists in preventing the formation of cold joints in large pours
- · Allows specified strength grades to be met at reduced cement content or increased workability

Uses

- To extend the setting time of concrete, extending working times
- To improve the effectiveness of the water content of a concrete mix
- In all types of low and high rise building
- Particularly suitable for use in mixes having fly ash and also improve the working life of semi dry concrete mixes, specifically RCC type of mixes

Confirm standard

• IS 9103:1999

Compliance standard

ASTM C494, AASHTO M 194, Type B

Method of Application

• The optimum dosage is best determined by site trials with the concrete mix. Site trials with PLASTCONE R should always be compared with mix containing no admixture. As a guide, a dosage range of 0.6 to 1.5% of cement is normally recommended.

Technical Information

PROPERTIES	RESULTS
Appearance	Brown Liquid
Sp. Gravity	1.05 to 1.07 @25°C
Air entrainment	Typically slightly less air will be entrained than in normal concrete mix
Chloride Content	Nil
Alkali Content	Typically less then 5 g Na20 equivalent per litre of admixture

This in turn leads to a series of associated benefits

- Enhanced durability: PLASTCONE R reduces the permeability and increases the resistance to weathering and enhances the durability.
- **Corrosivety:** Chloride free PLASTCONE R admixture will neither initiate nor promote corrosion of reinforced steel in concrete.
- Strength: Reduced water cement ratio will increase strength of concrete at all stages.

Over dosing

• An overdose of double the intended amount of PLASTCONE R will result in a significant increase in retardation as compared to that normally obtained at the intended dosage.

Curing

Normal good curing practice should be adopted.

Packaging

• PLASTCONE R is available in 50 & 250 kg containers.

Storage

• Minimum of 12 months shelf-life if kept under room temperature (i.e. 5°C to 45°C).

For selection of admixture

• As per your project please visit our smart store in www.redwop.net

Note: All technical data stated in this product data sheet are based on laboratory tests. Actual measured data may vary according to trails and quality of material availability.

REDWOP CHEMICALS PVT. LTD.