



PRIMER WB

Interior / exterior water base primer

Description

PRIMER WB is a water-based primer which imparts an aggressive, high tack finish on the treated substrate. It is specifically designed to facilitate tenacious adhesion of Interior/exterior water base primer is a superior quality, fast drying, water-based primer, sealer and stain blocker that provides excellent adhesion and a mildew resistant coating. It's ideal for use in moisture prone areas and blocks out most stains caused by water, tannin, ink, pencil, felt marker and grease. For use on interior and exterior surfaces.

Advantages

- Excellent adhesion bonds to substrate and binds dust
- Aggressive tack provides a tenacious bond to difficult substrates such as dens glass gold and other glass faced wall boards
- Fast drying increased flexibility for application schedule
- Fast and easy application by brush or roller
- VOC compliant water-based, contains no hazardous or flammable solvents
- Low odor no noxious fumes

Uses

- On properly prepared interior and exterior surfaces such as Concrete Block/CMU, Cement Board siding, brick, plaster, drywall/gypsum board, wood, plywood
- Non-Ferrous Metals
- Architectural Plastics
- Vinyl/PVC
- Fiberglass

Method of Application

- All surfaces must be free from frost, dirt, grease, oil or other contaminants
- Apply on coat of PRIMER WB by brushing after suitable thinning with water. Allow drying for 4 hours. Then apply recommended number of top coats. If significant dust or dirt accumulates on the primed surface, re-prime with a thin coat of PRIMER WB.
- Nap rollers have been found to be very successful for the application of PRIMER WB. A moderately thick coating should be applied and rolled out evenly.
- PRIMER WB Interior/Exterior Water-Base Primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying PRIMER WB Interior/Exterior Water-Base Primer.

Coverage

- 1 Coat 100-120 ft² per liter.

Packaging

- PRIMER WB is supplied in 1, 4, 10 and 20 liter container

Shelf Life

- Minimum of 24 months shelf-life if kept unopened under room temperature (i.e. 27°C).

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664