

# LAYOR Matt Bharat

Finishes for Interior Walls



### Description:

Layor - Matt Bharat provides a rich and matt finish to the wall due to its super-acrylic quality.

### Product Features:

#### Rich matt finish

Layor - Matt Bharat has a rich and smooth matt finish that oozes sophistication.

#### Stain Guard

Layor - Matt Bharat has been fortified with Stain Guard technology that guards your walls against most household stains and ensures easy cleanability.

#### Long lasting film

Layor - Matt Bharat has a long lasting film that keeps your house as good as new for a long time.

#### Fungus and mildew resistance

Layor - Matt Bharat is designed to protect your walls against unwanted fungus that can cause considerable damage.

#### Extra deep colours for feature walls

Layor - Matt Bharat offers a unique range of extra deep colours that helps you highlight your home's features bet

### Company Standard Compliance:



### Technical Information:

Properties	Specification
Color	Wide Range of Shades
Finish	Matt
Surface Drying Time	30 min
Sheen levels	2 - 5 at 60 deg GH
Flash point IS101/1987 Part 1, Sec 6	NA
Stability of thinned paint	To be used within 12 hours

### Direction For Use:

#### Pre Painting Steps

#### Plaster

New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

#### Cleaning

Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water.

#### Filling for Holes & Dents

In case of dents and holes use Redwops Acrylic Wall Putty or white cement and fine sand in the ratio 1:3.

## Application Procedure

Apply first coat of Laylor - Matt Bharat by brush/roller/spray. After 4 to 5 hours apply second coat of Laylor - Matt Bharat.

### Coverage:

On normal masonry surface after brushing  
1 COAT @150 - 170 sq.ft/ltr\*\*  
2 COATS @ 75 - 85 sq.ft/ltr\*\*

\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

### Packaging:

Laylor - Matt Bharat is supplied in 1ltr, 4 ltr & 20 ltr containers.

### Shelf-life:

3 years from date of manufacture in original tightly closed containers. Keep the container away from direct sunlight and excessive heat.

### Post Painting Care:


For best performance ensure dry dust cleaning at regular intervals. Allow drying time of 3 weeks for proper film formation before any sponge cleaning with mild soap solution.


## Precautions:

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not over-thin or over-extend the brush.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.


## Health & Safety:


- Kindly refer to the MSDS for Laylor - Matt Bharat which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

	This symbol is used to identify Redwop products which give off a low level of volatile organic compounds (VOC) as certified by GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.), an international organisation for controlling the level of emissions from products used for floors.
---	--


 CML-7600053713	This symbol identifies that the products maintain their parameter with consistency & checked frequently as per BIS department and provided quality assurance.
---	---


	Our Commitment To The Environment Redwop products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.
---	---

	ISO/IEC 17025 enables laboratories to demonstrate that they operate competently and generate valid results, thereby promoting confidence in their work both nationally and around the world.
---	--

	It is the practice of increasing efficiency with which buildings use resources- energy, water and materials-while reducing building impacts on human health and the environment.
---	--

	ISO 45001 is the world's international standard for occupational health and safety, issued to protect employees and visitors from work-related accidents and diseases.
---	--

	ISO 9001:2015 is a globally recognized standard for quality management systems (QMS). It helps organizations of all sizes and sectors to: Improve performance, Meet customer expectations, Demonstrate commitment to quality, and Identify and improve processes that lack consistency.
---	---

	ISO 14001 is the internationally recognized standard for environmental management systems (EMS). It provides a framework for organizations to design and implement an EMS, and continually improve their environmental performance
---	--