

REDOPOXY THINNER

EPOXY THINNER

Description

REDOPOXY THINNER is a mixture of properly selected organic solvents intended for thinning epoxy products. It is a blend of solvents formulated for use as an epoxy thinner. It can be used for effective cleaning paint spray guns and tools from the residues of epoxy products.

Uses

- Specifically formulated as an epoxy reducer.
- To clean equipment e.g., paint rollers, brushes etc.
- Epoxy paints
- Epoxy primers

Technical Information

Properties	Specification
Appearance	Colorless Liquid
Specific Gravity	0.90±0.05
Flash Point	29°C

Application Condition

Mixing. Ready for use.
Only use in proportion specified. Do not exceed quantity.

Application Information

Use as recommended solvent described in individual product datasheets.
Do not use in polyurethanes

Packaging

REDOPOXY THINNER is available in 20 lit pack.

Shelf Life & Storage

REDOPOXY THINNER has a shelf-life of 24 months from date of manufacturing. Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight.

Health & Safety

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.
- Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.
- Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- Refer to Safety Data Sheet for complete information.

Disclaimer

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be dependable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Note: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664