

WOLFEX Vande Bharat

Finishes for Walls



Description:

Wolfex Vandebharat is a best-in-class interior paint. The latex technology provides film strength better than Distempers. It offers smooth Latex finish at a price of Distempers. Higher washability allows Wolfex Vandebharat to last longer compared to Distemper.

Product Features:

- The latex technology makes it easier for painters to apply, provides better flow levelling and hence providing smooth finish.
- Available in a wide range of shades
- Low Washability

Company Standard Compliance:



Technical Information:

Properties	Specification
Finish	Matt
Surface Drying time	30 min
Sheen levels	2 - 5 at 60°GH
Flash point (IS 101/1987 Part 1, Sec 6)	NA
Stability of thinned paint	To be used within 24 hours

Direction for Use:

PLASTER:

New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING:

Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water.

FILLING FOR CRACKS:

For filling cracks upto 3mm use Redwops Seal Crack FILLING FOR HOLES & DENTS In case of dents and holes use Redwop Wall Putty or white cement and fine sand in the ratio 1:3

APPLICATION PROCEDURE:

Apply 1st coat of Wolfex Vandebharat by brush/roller. After 4-6 hours apply 2nd coat of Wolfex Vandebharat.

Coverage:

On normal masonry surface after Brushing + Rolling (Foam Roller) 2 COATS @ 90 - 110 Sq.ft/Kg**

Packaging:

WOLFEX VANDEBHARAT is supplied in 2kg, 5kg, 10kg, and 20 kg containers.

Shelf-life:

3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.




Precautions:

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or over-extend the brush.
- Tint using Redwops machine colourants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.

Health & Safety:

- Kindly refer to the MSDS for Wolfex Vandebharat which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables.
- May be harmful if swallowed.
- In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

	It is the practice of increasing efficiency with which buildings use resources- energy, water and materials-while reducing building impacts on human health and the environment.
	ISO 45001 is the world's international standard for occupational health and safety, issued to protect employees and visitors from work-related accidents and diseases.
	ISO 9001:2015 is a globally recognized standard for quality management systems (QMS). It helps organizations of all sizes and sectors to: Improve performance, Meet customer expectations, Demonstrate commitment to quality, and Identify and improve processes that lack consistency.
	ISO 14001 is the internationally recognized standard for environmental management systems (EMS). It provides a framework for organizations to design and implement an EMS, and continually improve their environmental performance.

	This symbol is used to identify Redwop products which give off a low level of volatile organic compounds (VOC) as certified by GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.), an international organisation for controlling the level of emissions from products used for floors.
	Our Commitment To The Environment Redwop products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.
	ISO/IEC 17025 enables laboratories to demonstrate that they operate competently and generate valid results, thereby promoting confidence in their work both nationally and around the world.