

Redwop[®]
INNOVATING FOR A BETTER WORLD



ACRYLIC DISTEMPER



WOLFEX

Acrylic Distemper

Description

WOLFEX is an acrylic distemper. It is water based distemper for exterior/interior wall surface to give a smooth finish. It is based on acrylic emulsion to give durability and decoration to the walls. It is available in white color shade, which gives a bright look to the wall.

Advantages

- Excellent adhesion and bonds to the substrate
- Provides a tenacious bond to difficult substrates such as dense glass and other glass faced wall boards
- Fast drying
- Environment friendly
- Anti-chalking
- Increased flexibility for application schedule
- Easy application
- Water-based, contains no hazardous or flammable solvents
- Less odor having no noxious fumes

Uses

- On internal and external wall plaster
- Bricks wall

Technical Information

PROPERTIES	RESULTS
Appearance	white
Compatible with Tints	Yes
Durability	Yes
Drying time	15 minutes
Flammable	No

Method of Application

- All surfaces must be preferably dry and free from oil, loose particles and laitance.
- Scrape off loose paint and sand to a smooth surface.
- Sanding or removal of paint containing lead is hazardous. Unpainted, exterior wood exposed to sun and/or moisture longer than 2-4 weeks must be cleaned and sanded before priming.
- Combine WOLFEX and glue as per requirement than colour with tints as per your demand of colors.
- Slowly add water to WOLFEX, mixing the contents thoroughly. Normally, 500-600 ml water is required for 1 kg WOLFEX.
- Apply 2-3 coats by brush, roller or spray with an interval of 4-6 hours between coats.

Packaging

- WOLFEX is supplied in 1kg, 2kg, 5kg, 10kg, and 20 kg containers.

Shelf Life

- 24 months shelf life when stored below 25°C in original unopened containers.

REDWOP CHEMICALS PVT. LTD.

Head office: 2nd Floor, Pearl plaza Complex, B/S GT Sheth School, Near KKV Hall, 150ft Ring Road, Rajkot- Pin.360005 Gujarat, India.

✉ info@redwop.net

🌐 www.redwop.net

☎ +91 97246 55551

☎ +91 281 2576664